


Cavi

Cables

Kabel

Cavi acciaio zincato
Galvanized steel cables
Verzinkter Stahl Kabel



Terminale
Nipple
Nippel

Portata di sicurezza
Safety load
Zuglast

	Ø		Terminale	Portata di sicurezza
L3N	Ø 1 mm	19	□ Ø 3x3 mm	40 kg
L4N	Ø 1 mm	19	□ Ø 4x4 mm	50 kg
L3S	Ø 1 mm	49	□ Ø 3x3 mm	40 kg
L4S	Ø 1 mm	49	□ Ø 4x4 mm	50 kg
NGW	Ø 1,2 mm	19	□ Ø 3x3 mm	50 kg
GTW	Ø 1,2 mm	19	□ Ø 4x4 mm	80 kg
GTW mm SF55	Ø 1,2 mm	19	○ Ø 5,5 mm	80 kg
SGW	Ø 1,2 mm	49	□ Ø 3x3 mm	50 kg
S4W	Ø 1,2 mm	49	□ Ø 4x4 mm	80 kg
SGW mm SF55	Ø 1,2 mm	49	○ Ø 5,5 mm	80 kg
W mm 160G	Ø 1,5 mm	19	□ Ø 4x4 mm	150 kg
W mm 160N	Ø 1,5 mm	19	○ Ø 5,5 mm	150 kg
WS mm 160G	Ø 1,5 mm	49	□ Ø 4x4 mm	100 kg
WS mm 160N	Ø 1,5 mm	49	○ Ø 5,5 mm	100 kg

Cavi

Cables

Kabel

Cavi acciaio inox
Stainless steel
Edelstahl Kabel



Terminale
Nipple
Nippel

Portata di sicurezza
Safety load
Zuglast

	Ø		Terminale	Portata di sicurezza
L3NX	Ø 1 mm	19	□ Ø 3x3 mm	30 kg
L4NX	Ø 1 mm	19	□ Ø 4x4 mm	40 kg
L3SX	Ø 1 mm	49	□ Ø 3x3 mm	30 kg
L4SX	Ø 1 mm	49	□ Ø 4x4 mm	40 kg
NGWX	Ø 1,2 mm	19	□ Ø 3x3 mm	50 kg
GTWX	Ø 1,2 mm	19	□ Ø 4x4 mm	60 kg
GTWX mm SF55	Ø 1,2 mm	19	○ Ø 5,5 mm	60 kg
SGWX	Ø 1,2 mm	49	□ Ø 3x3 mm	50 kg
S4WX	Ø 1,2 mm	49	□ Ø 4x4 mm	60 kg
SGWX mm SF55	Ø 1,2 mm	49	○ Ø 5,5 mm	60 kg
W4X mm 160G	Ø 1,5 mm	19	□ Ø 4x4 mm	120 kg
WX mm 160N	Ø 1,5 mm	19	○ Ø 5,5 mm	120 kg
WSX mm 160G	Ø 1,5 mm	49	□ Ø 4x4 mm	90 kg
WSX mm 160N	Ø 1,5 mm	49	○ Ø 5,5 mm	90 kg

